HP StorageWorks

4000/6000/8000 Enterprise Virtual Array connectivity 5.0A for OpenVMS release notes



Part number: 5697–5262 Second edition: May 2005

Legal and notice information

Copyright © 2005 Hewlett-Packard Development Company, L.P.

Hewlett-Packard Company makes no warranty of any kind with regard to this material, including, but not limited to, the implied warranties of merchantability and fitness for a particular purpose. Hewlett-Packard shall not be liable for errors contained herein or for incidental or consequential damages in connection with the furnishing, performance, or use of this material.

This document contains proprietary information, which is protected by copyright. No part of this document may be photocopied, reproduced, or translated into another language without the prior written consent of Hewlett-Packard. The information is provided "as is" without warranty of any kind and is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

4000/6000/8000 Enterprise Virtual Array connectivity 5.0A for OpenVMS release notes

About this document

This section describes the content reflected in this document, including:

- Release notes information
- Intended audience

Release notes information

These release notes cover the following topics:

- New features
- EVA storage system
- EVA compatability
- Operating constraints
- Storage System Scripting Utility for EVA
- Avoiding problem situations

Intended audience

This document is intended for use by:

- Customers who purchased the HP StorageWorks 4000/6000/8000 Enterprise Virtual Array (EVA) and the OpenVMS operating system
- HP customer service personnel responsible for installing and maintaining devices connected to the EVA storage system

Accessing future product updates

HP strongly recommends that customers sign up online using the Subscriber's choice web site:

http://www.hp.com/go/e-updates.

- Subscribing to this service provides you with e-mail updates on the latest product enhancements, newest versions of drivers, and firmware documentation updates as well as instant access to numerous other product resources.
- After signing up, you can quickly locate your products by selecting Business support and then Storage under Product Category.

New features

This release includes the following includes support for the EVA4000/6000/8000 controller software 5.02.

EVA storage system

This document contains the most recent product information about operating the EVA on a system running OpenVMS.

EVA documentation

For a complete library of EVA and related documentation, see the following web sites:

http://www.hp.com/go/eva4000

http://www.hp.com/go/eva6000

http://www.hp.com/go/eva8000

Supported configurations

Supported configurations are described in the *Enterprise Virtual Array QuickSpecs*; see the following web site:

http://h18006.www1.hp.com/storage/arraysystems.html.

The extended interoperability of the heterogeneous SAN allows you to mix several types of HP StorageWorks storage systems. The HP StorageWorks SAN design reference guide is a detailed guide for SAN configurations and is available at the following web site:

http://h18004.www1.hp.com/products/storageworks/san/documentation.html.

EVA compatibility

Operating system support

Table 1 lists the operating system's specifications.



NOTE:

Table 1 contains current minimum-level operating system specifications at the time of the EVA 5.02 release. Some component versions may change due to revision. For the latest information, see the following web site: http://h18006.www1.hp.com/storage/index.html.

Table 1 Operating system specifications

OpenVMS version	Fibre SCSI ECO kit	
OpenVMS 7.3-2	DEC-AXPVMS_VMS732_FIBRE _SCSI_V0400	

For the current Fibre SCSI ECO kit for OpenVMS, see the following HP IT Resource Center web site:

http://www.itrc.hp.com.

FCA support

Table 2 lists the supported Fibre Channel Adapters (FCAs) and the required firmware versions.

Table 2 FCA (HBA) Support

FCA (HBA)	Driver	Adapter firmware (minimum)	
HP StorageWorks DS-KGPSA-CA 1Gb, 64-bit/33MHz PCI	Native	3.92a2	
HP StorageWorks DS-KGPSA-DA 2Gb, 64-bit/66MHz PCI	Native	3.92α2	
HP StorageWorks DS-KGPSA-EA 2Gb, 64-bit/133MHz PCI-X	Native	1.90a4	
HP StorageWorks DS-A5132-AA 2Gb, 64-bit/133MHz PCI-X	Native	1.90a4	
HP StorageWorks DS-A5134-AA 2Gb, 64-bit/133MHz PCI-X Dual	Native	1.90a4	

Switch support

This release supports the Fibre Channel switches and firmware versions listed in the HP StorageWorks SAN design reference guide which can be downloaded from the following web site:

http://h18000.www1.hp.com/products/storageworks/san/documentation.html.



NOTE:

HP recommends that you do not mix switch firmware versions in your SAN. It is considered a best practice to uniformly upgrade all switches in the SAN.

Alpha servers support

Table 3 lists the EVA-compatible Alpha servers.

Table 3 EVA-compatible Alpha servers

Alpha Server	DS-KGPSA-CA support	DS-KGPSA-DA support	DS-KGPSA-EA support	DS-A51321-AA support	DS-A5134-AA support
DS10	Yes	Yes	Yes	No	No
DS15	No	Yes	Yes	Yes	Yes
DS20E	Yes	Yes	Yes	Yes	No
DS25	Yes	Yes	Yes	Yes	Yes
ES40	Yes	Yes	Yes	Yes	No
ES45	Yes	Yes	Yes	Yes	Yes
ES47	No	Yes	Yes	Yes	Yes
ES80	No	Yes	Yes	Yes	Yes
G\$80	Yes	Yes	Yes	Yes	No
G\$160	Yes	Yes	Yes	Yes	No
G\$320	Yes	Yes	Yes	Yes	No
GS1280	No	Yes	Yes	Yes	Yes

Multiple-path support

Multiple-path capability is integrated into the OpenVMS operating system. No additional software is required to achieve high-availability multpathing capability.

Single-path support

OpenVMS servers require a single FCA to support single-path mode.



NOTE:

Single-path mode should not be used in mission critical environments.

Operating constraints

You can find information about operating constraints specific to the EVA and Command View EVA in their respective release notes.



NOTE:

The AlpaServer console firmware will only recognize *four* of the eight available boot paths to the EVA400/6000/8000 storage system. This issue is addressed in the 7.0 AphaServer console release. The operating system, once booted will recognize all available paths.

Failover/failback

Failback preference settings for the HSV controllers are specific to the operating system. Refer to the HP StorageWorks Enterprise Virtual Array release notes for details.

Storage System Scripting Utility for EVA

The HP StorageWorks Command View EVA software includes a Storage System Scripting Utility (SSSU). You can download the HP StorageWorks Command View EVA with SSSU from the following HP web site:

http://h18006.www1.hp.com/products/storage/software/cmdvieweva/index.html.



NOTE:

The minimum version of the HP StorageWorks Command View EVA 4000/6000/8000 is 4.0.

Avoiding problem situations

You can find information about problems specific to the EVA and Command View EVA and the solutions in their respective release notes.